

Safety Data Sheet

Section 1. Identification of the substance/mixture and of the company/undertaking

Product identifier:

Product name: Methyl acrylate

Reference number(SDS):10140jis_E-3

Product type:

Reagent

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the product: Research and Development

Uses advised against: Do not use for other purposes.

Details of the supplier of the safety data sheet

Manufacturer/Supplier: JUNSEI CHEMICAL CO., LTD.

Address: 1-6, Ohmano-cho, Koshigaya-shi, Saitama 343-0844, Japan

Division: Quality Assurance Department

Telephone number: +81-48-986-6161

FAX: +81-48-989-2787

e-mail address: shiyaku-t@junsei.co.jp

Section 2. Hazards identification

GHS classification and label elements of the product**Classification of the substance or mixture****PHYSICAL AND CHEMICAL HAZARDS**

Flammable liquids: Category 2

Self-reactive substances and mixtures: Type G

HEALTH HAZARDS

Acute toxicity (Oral): Category 4

Acute toxicity (Dermal): Category 4

Acute toxicity (Inhalation): Category 3

Skin corrosion/irritation: Category 1

Serious eye damage/eye irritation: Category 1

Skin sensitization: Category 1A

Carcinogenicity: Category 1B

Specific target organ toxicity – single exposure: Category 3 (Respiratory tract irritation)

Specific target organ toxicity – repeated exposure: Category 1 (respiratory organs)

ENVIRONMENT HAZARDS

Hazardous to the aquatic environment, short-term (acute): Category 2

Hazardous to the aquatic environment, long-term (chronic): Category 2

(Note) GHS classification without description: Not classified/Classification not possible

Label elements

Signal word: Danger

HAZARD STATEMENT

H225-Highly flammable liquid and vapor
H302-Harmful if swallowed
H312-Harmful in contact with skin
H331-Toxic if inhaled
H314-Causes severe skin burns and eye damage
H318-Causes serious eye damage
H317-May cause an allergic skin reaction
H350-May cause cancer
H335-May cause respiratory irritation
H372-Causes damage to organs through prolonged or repeated exposure
H401-Toxic to aquatic life
H411-Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENT**Prevention**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid release to the environment.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe vapors.
Use only outdoors or in a well-ventilated area.
Wash contaminated parts thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
Do not eat, drink or smoke when using this product.

Response

In case of fire: Use foam, dry powder, CO2 to extinguish.
Collect spillage.
Specific treatment is required.
Get medical advice/attention if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
Immediately call a POISON CENTER/doctor/physician.
Call a POISON CENTER/doctor/physician.
Call a POISON CENTER/doctor/physician if you feel unwell.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Take off contaminated clothing and wash it before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Rinse mouth.
IF SWALLOWED: Call a POISON CENTER/doctor/physician if you feel unwell.

Methyl acrylate, JUNSEI CHEMICAL CO., LTD., 10140jis_E-3, 02/May/2025

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Store locked up.

Disposal

Dispose of contents/container in accordance with local/national regulation.

Specific Physical and Chemical hazards

Highly flammable liquid. Vapor/air mixture may explode.

Section 3. Composition/information on ingredients**Mixture/Substance selection:****Substance**

Common name, synonyms: Methyl-2-propenoate

Ingredient name: Methyl acrylate

Content (%): 99.0 <

Chemical formula: C₄H₆O₂

ENCS: 2-987

CAS No.: 96-33-3

MW: 86.09

EC No.: 202-500-6

Note : The figures shown above are not the specifications of the product.

Stabilizing additives

Stabilizer : Hydroquinone monomethyl ether 300ppm

Section 4. First-aid measures**Descriptions of first-aid measures****General measures**

Get medical advice/attention if you feel unwell.

Immediately call a POISON CENTER/doctor/physician.

Keep victim warm and quiet.

Call emergency medical service.

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

IF INHALED

Remove person to fresh air and keep comfortable for breathing.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

Call a POISON CENTER/doctor/physician.

IF INHALED: Call a POISON CENTER/doctor/physician if you feel unwell.

IF ON SKIN (or hair)

Take off immediately all contaminated clothing. Rinse skin with water or shower.

Gently wash with plenty of soap and water.

Wash with plenty of soap and water.

In case of burns, immediately cool affected skin for as long as possible with cold water.

Do not remove clothing if adhering to skin.

Immediately call a POISON CENTER/doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Remove and isolate contaminated clothing and shoes.

IF IN EYES

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor/physician.

If eye irritation persists: Get medical advice/attention.

IF SWALLOWED

Rinse mouth. Do NOT induce vomiting.

If victim is conscious, give 1 – 2 glasses of water.

IF SWALLOWED: Call a POISON CENTER/doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

(Symptoms when inhalation or ingestion)

Cough. Shortness of breath. Sore throat. Abdominal pain. Diarrhoea. Nausea. Vomiting.

(Symptoms when skin and/or eye contact)

Redness of the skin. Pain. Redness of the eyes.

Indication of any immediate medical attention and special treatment needed

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

In case of fire, use foam, dry powder, CO2 to extinguish.

Unsuitable extinguishing media

Do not use direct water jet.

Specific hazards arising from the substance or mixture

Containers may explode when heated.

Fire may produce irritating, corrosive and/or toxic gases.

Runoff from fire control or dilution water may cause pollution.

Advice for firefighters**Specific fire-fighting measures**

Evacuate non-essential personnel to safe area.

Cool container with water spray.

Special protective equipment and precautions for fire-fighters

Wear fire resistant or flame retardant clothing.

Wear protective gloves/protective clothing/eye protection/face protection.

Firefighters should wear self-contained breathing apparatus with a full facepiece operated in the positive pressure mode.

Section 6. Accidental release measures**Personnel precautions, protective equipment and emergency procedures**

Keep unauthorized personnel away.

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

Ventilate area until material pick up is complete.

Wear proper protective equipment.

PUBLIC SAFETY: Ventilate closed spaces before entering.

Do not touch or walk through spilled material.

Consider initial downwind evacuation for at least 300 meters (1000 feet).

Environmental precautions

Runoff to sewer may create fire or explosion hazard.

Vapor explosion hazard indoors, outdoors or in sewers.

Avoid release to headsprings, rivers, lakes, ocean and groundwater.

Methods and materials for containment and cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material.

All equipment used when handling the product must be grounded.

Collect leaking and spilled liquid in covered containers as far as possible.

Preventive measures for secondary accident

Collect spillage.

Stop leak if you can do it without risk.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Prevent entry into waterways, sewers, basements or confined areas.

Section 7. Handling and storage

Precautions for safe handling

Preventive measures

(Exposure Control for handling personnel)

Do not breathe vapors.

(Protective measures against fire and explosion)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

(Exhaust/ventilator)

Exhaust/ventilator should be available.

(Safety treatments)

Avoid contact with skin.

Avoid contact with eyes.

Safety Measures

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

When using do not eat, drink or smoke.

Any incompatibilities

Strong acids, Strong bases, Strong oxidizing agents, Peroxides should not be mixed with the chemicals.

Advice on general occupational hygiene

Wash contaminated parts thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash it before reuse.

Storage

Conditions for safe storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Protect from sunlight.

Store in accordance with local/national regulation.

Store locked up.

Container and packaging materials for safe handling data is not available.

Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See

Section 8 for exposure controls and personal protection recommendations.

Section 8. Exposure controls/personal protection**Control parameters**

Control value and Concentration standard value under ISHA

Concentration standard value TWA: 2ppm

Occupational Exposure Limit

JSOH

2ppm; 7mg/m³

ACGIH

TWA: 2ppm (Eye, skin & URT irr; eye dam)

Notation

Skin; DSEN

Exposure controls

Appropriate engineering controls

Do not use in areas without adequate ventilation.

Eye wash station should be available.

Washing facilities should be available.

Individual protection measures

Respiratory protection

Select and wear respiratory protection in accordance with approved standards (e.g. JIS T8150).

Recommended respiratory protection: Gas mask

Hand protection

Wear protective gloves.

Inspect before use and replace worn or damaged gloves.

Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions.

Chemical-resistant, impervious gloves complying with an approved standard (e.g. JIS T8116) should be used.

Eye protection

Wear chemical safety goggle.

Wear eye/face protection in accordance with approved standards (e.g. JIS T8147).

Skin and body protection

Wear impervious clothing and boots in case of repeated or prolonged treatment.

Personal protective equipment for the body and skin should be selected based on the task being performed and the risks involved.

Section 9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical state: Liquid

Color: Colorless

Odor: Irritant odor

Odor threshold data is not available.

Melting point/Freezing point: -76.5°C

Boiling point or initial boiling point: 80.5°C

Boiling range data is not available.

Flammability (gases, liquids and solids) data is not available.

Lower and upper explosion limit/flammability limit:

Lower explosion limit: 2.8 vol %

Upper explosion limit: 25 vol %

Flash point: $-2.8^{\circ}\text{C}(\text{C.C.})$

Auto-ignition temperature: 468°C

Decomposition temperature data is not available.

Self-Accelerating Decomposition Temperature/SADT data is not available.

pH data is not available.

Dynamic viscosity: $0.472\text{mPa}\cdot\text{s}(25^{\circ}\text{C})$

Kinematic viscosity data is not available.

Solubility:

Solubility in water: 6 g/100 mL (20°C)

Solubility in solvent data is not available.

n-Octanol/water partition coefficient: $\log \text{Pow} 0.8$

Vapor pressure: 9.1 kPa (20°C)

Vapor density data is not available.

Density and/or relative density: $0.954\sim 0.959\text{ g/mL}(20^{\circ}\text{C})$

Relative vapor density (Air=1): 3.0

Relative density of the Vapor/air - mixture at 20°C (Air = 1): 1.18

Particle characteristics data is not available.

Other information

Critical temperature data is not available.

Evaporation rate data is not available.

VOC data is not available.

Section 10. Stability and Reactivity

Reactivity

Runaway polymerization may occur without stabilizer/inhibitor or when heated.

Chemical stability

Stable under normal storage/handling conditions.

Highly flammable.

Possibility of hazardous reactions

The vapour is heavier than air and may travel along the ground; distant ignition possible.

The substance may spontaneously polymerize due to warming, under the influence of light and

Methyl acrylate, JUNSEI CHEMICAL CO., LTD., 10140jis_E-3, 02/May/2025

on contact with peroxides.

Reacts violently with strong acids, strong bases and strong oxidants. This generates fire and explosion hazard.

Conditions to avoid

Contact with incompatible materials.

Open flames. Heating. Sparks. Light.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Peroxides.

Hazardous decomposition products

Carbon oxides.

Section 11. Toxicological Information

Information on toxicological effects

Acute toxicity

Acute toxicity (Oral)

[Product]

Category 4, Harmful if swallowed

[Data for components of the product]

[NITE-CHRIP]

rat LD50: 768 mg/kg (OECD TG 401, GLP) (source: NITE)

Acute toxicity (Dermal)

[Product]

Category 4, Harmful in contact with skin

[Data for components of the product]

[NITE-CHRIP]

rabbit LD50: 1.3 mL/kg (a converted value: 1239 mg/kg) (source: NITE)

Acute toxicity (Inhalation)

[Product]

Category 3, Toxic if inhaled

[Data for components of the product]

[NITE-CHRIP]

vapor: rat LC50: 1000 ppm (4-hour) (source: NITE)

Irritant properties

Skin corrosion/irritation

[Product]

Category 1, Causes severe skin burns and eye damage

[Data for components of the product]

[NITE-CHRIP]

Category 1 (source: NITE)

Serious eye damage/irritation

[Product]

Category 1, Causes serious eye damage

[Data for components of the product]

[NITE-CHIRP]

Category 1 (source: NITE)

Sensitization

Respiratory sensitization

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Skin sensitization

[Product]

Category 1A, May cause an allergic skin reaction

[Data for components of the product]

[NITE-CHIRP]

Category 1A (source: NITE)

Germ cell mutagenicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Carcinogenicity

[Product]

Category 1B, May cause cancer

[Data for components of the product]

[NITE-CHIRP]

Category 1B (source: NITE)

[IARC]

Group 2B : Possibly carcinogenic to humans

[ACGIH]

A4: Not Classifiable as a Human Carcinogen

[JSOH]

Group 2B: The agents which are probably or possibly carcinogenic to humans

Reproductive toxicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Specific target organ toxicity (STOT)

STOT-single exposure

[Product]

Category 3, May cause respiratory irritation

[Data for components of the product]

[NITE-CHIRP]

Category 3 (Respiratory tract irritation) (source: NITE)

STOT-repeated exposure

[Product]

Category 1, Causes damage to organs through prolonged or repeated exposure

[Data for components of the product]

[NITE-CHRIP]

Category 1 (respiratory organs) (source: NITE)

Aspiration hazard

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Section 12. Ecological Information

Ecotoxicity

Aquatic toxicity

[Product]

Category 2, Toxic to aquatic life

Category 2, Toxic to aquatic life with long lasting effects

[Data for components of the product]

Hazardous to the aquatic environment, short-term (acute)

[NITE-CHRIP]

Fish (*Cyprinodon variegatus*) 96-hour LC50: 1.1 mg/L (source: NITE)

Hazardous to the aquatic environment, long-term (chronic)

[NITE-CHRIP]

Crustacea (*Daphnia magna*) 21-day NOEC: 0.36 mg/L (source: NITE)

Water solubility

[Data for components of the product]

6 g/100 mL (20°C) (source: ICSC, 2003)

Persistence and degradability

[Data for components of the product]

Not rapidly degradable (Degradation rate: 59.8% (by BOD)) (OECD TG 301D, GLP) (source: NITE)

Bioaccumulative potential

[Data for components of the product]

log Pow: 0.8 (source: ICSC, 2003)

Mobility in soil

Mobility in soil data is not available.

Other adverse effects

Ozone depleting chemical data is not available.

Section 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Waste treatment methods

Methyl acrylate, JUNSEI CHEMICAL CO., LTD., 10140jis_E-3, 02/May/2025

Avoid release to the environment.

Dispose of contents/container in accordance with local/national regulation.

Section 14. Transport Information**UN No., UN CLASS**

UN Number or ID Number : 1919

UN Proper Shipping Name :

METHYL ACRYLATE, STABILIZED

Class or division (Transport hazard class) : 3

Packing group : II

ERG GUIDE No.: 129P

Special provisions No.: 386

IMDG Code (International Maritime Dangerous Goods Regulations)

UN Number or ID Number : 1919

UN Proper Shipping Name :

METHYL ACRYLATE, STABILIZED

Class or division (Transport hazard class) : 3

Packing group : II

Special provisions No.: 386

IATA (Dangerous Goods Regulations)

UN Number or ID Number : 1919

UN Proper Shipping Name :

METHYL ACRYLATE, STABILIZED

Class or division (Transport hazard class) : 3

Hazard labels : Flamm. liquid

Packing group : II

Special provisions No.: A209

Environmental hazards

Marine pollutants (yes/no) : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Noxious Liquid Substances ; Cat. Y

Methyl acrylate

MARPOL Annex V – HME (Harmful to the Marine Environment)

Carcinogenicity: cat.1, 1A, 1B

Methyl acrylate

Specific target organ toxicity – repeated exposure: cat.1

Methyl acrylate

Hazardous to the aquatic environment – long-term (chronic): cat.1, 2

Methyl acrylate

Section 15. Regulatory Information**Safety, health and environmental regulations/legislation specific for the substance or mixture****U.S. Toxic Substances Control Act (TSCA) Inventory**

Chemicals listed in TSCA Inventory

96-33-3

All components are listed or exempted.

Superfund Amendments and Reauthorizations Act (SARA), Title III

SARA 313 (TRI)

Methyl acrylate

Other regulatory information

We are not able to check up the regulatory information with regard to the substances in your country or region, therefore, we request this matter would be filled by your responsibility.

Regulatory information with regard to this substance in your country or in your region should be examined by your own responsibility.

Ensure this material in compliance with federal requirements and ensure conformity to local regulations.

Regulatory information in this section are limited to intentional ingredient(s), but does not contain information on non-intentional ingredients or impurities which are not informed by supplier(s).

Chemical safety assessment

Advice on safe handling for this product can be found in sections 7 and 8 of this SDS.

Section 16. Other information

GHS classification and labelling

H225-Flammable liquids, Category 2: H225 Highly flammable liquid and vapour

Self-Reactive Substances and Mixtures, Type G

H302-Acute toxicity, Category 4: H302 Harmful if swallowed

H312-Acute toxicity, Category 4: H312 Harmful in contact with skin

H331-Acute toxicity, Category 3: H331 Toxic if inhaled

H314-Skin corrosion/irritation, Category 1: H314 Causes severe skin burns and eye damage

H318-Serious eye damage/eye irritation, Category 1: H318 Causes serious eye damage

H317-Skin sensitization, Category 1A: H317 May cause an allergic skin reaction

H350-Carcinogenicity, Category 1B: H350 May cause cancer

H335-STOT – single exposure, Category 3, Respiratory tract irritation: H335 May cause respiratory irritation.

H372-STOT – Repeated exposure, Category 1: H372 Causes damage to organs through prolonged or repeated exposure

H401-Hazardous to the aquatic environment, short-term (acute), Category 2: H401 Toxic to aquatic life

H411-Hazardous to the aquatic environment, long-term (chronic), Category 2: H411 Toxic to aquatic life with long lasting effects

References and sources for data

Globally Harmonized System of classification and labelling of chemicals, UN

Recommendations on the TRANSPORT OF DANGEROUS GOODS 23rd edit., 2023 UN

IMDG Code, 2024 Edition (Incorporating Amendment 42-24)

IATA Dangerous Goods Regulations (66th Edition) 2025

2024 EMERGENCY RESPONSE GUIDEBOOK (US DOT)

2025 TLVs and BEIs. (ACGIH)

JIS Z 7252 : 2019

JIS Z 7253 : 2019

2024 Recommendation on TLVs (JSOH)

Notification No. 0111-1 (January 11, 2022), Chemical Hazards Control Division, Industrial Safety and Health Department, Labour Standards Bureau, MHLW in Japan

Supplier's data/information

Chemicals safety data management system "GHS Assistant" Version 4.33

(<https://www.asahi-ghs.com/>)

Methyl acrylate, JUNSEI CHEMICAL CO., LTD., 10140jis_E-3, 02/May/2025

NITE Chemical Risk Information Platform "NITE-CHRIP"

(https://www.chem-info.nite.go.jp/chem/chrip/chrip_search/systemTop)

GHS Classification Guidance for Enterprises 2019 Revised Edition (Ver. 2.1) (May. 2024, METI)

Abbreviations and acronyms

SDS (Safety Data Sheet)

LD50 (Lethal Dose, 50%)

LC50 (Lethal Concentration, 50%)

IARC (International Agency for Research on Cancer)

ACGIH (American Conference of Governmental Industrial Hygienists)

EPA (US Environmental Protection Agency)

NTP (US National Toxicology Program)

METI (Ministry of Economy, Trade and Industry in Japan)

MHLW (Ministry of Health, Labour and Welfare in Japan)

MOE (Ministry of the Environment in Japan)

JSOH (Japan Society for Occupational Health)

ISHA (Industrial Safety and Health Act in Japan)

CSCL (Chemical Substances Control Law in Japan)

EU (European Union)

EC50 (Effective Concentration, 50%)

NOEC (No Observed Effect Concentration)

BOD (Biochemical Oxygen Demand)

COD (Chemical Oxygen Demand)

BCF (Bioconcentration Factor)

anh (anhydride)

General Disclaimer

This data sheet was created based on the information we currently have and may be revised according to new information. In addition, the precautions apply only to normal handling, and in the case of special handling, please make adequate countermeasure to maintain your safety.

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the products' properties.

The GHS classification data given here is based on current Data published in Japan (National Institute of Technology and Evaluation (NITE) Chemical Risk Information Platform (NITE-CHRIP), up to FY2023).