

Safety Data Sheet

Section 1. Identification of the substance/mixture and of the company/undertaking

Product identifier:

Product name: Ethylbenzene

Reference number(SDS):17285jis_J_E2-3

Product type:

Reagent

Recommended use of the chemical and restrictions on use

Recommended uses: Research and Development

Restrictions on uses: Do not use for other purposes.

Details of the supplier of the safety data sheet

Manufacturer/Supplier: JUNSEI CHEMICAL CO., LTD.

Address: 1-6, Ohmano-cho, Koshigaya-shi, Saitama 343-0844, Japan

Division: Quality Assurance Department

Telephone number: +81-48-986-6161

FAX: +81-48-989-2787

e-mail address: shiyaku-t@junsei.co.jp

Section 2. Hazards identification

Classification of the substance or mixture**PHYSICAL AND CHEMICAL HAZARDS**

Flammable liquids: Category 2

HEALTH HAZARDS

Acute toxicity (Inhalation): Category 4

Serious eye damage/eye irritation: Category 2B

Carcinogenicity: Category 2

Reproductive toxicity: Category 1B

Specific target organ toxicity – single exposure: Category 3 (Respiratory tract irritation)

Specific target organ toxicity – single exposure: Category 3 (Narcotic effects)

Specific target organ toxicity – repeated exposure: Category 1 (auditory organ, nervous system)

Aspiration hazard: Category 1

ENVIRONMENT HAZARDS

Hazardous to the aquatic environment, short-term (acute): Category 1

Hazardous to the aquatic environment, long-term (chronic): Category 2

(Note) GHS classification without description: Not classified/Classification not possible

Label elements**Hazard pictograms:**

Signal word: Danger

Hazard statements

H225-Highly flammable liquid and vapor

- H332–Harmful if inhaled
- H320–Causes eye irritation
- H351–Suspected of causing cancer
- H360–May damage fertility or the unborn child
- H335–May cause respiratory irritation
- H336–May cause drowsiness or dizziness
- H372–Causes damage to organs through prolonged or repeated exposure
- H304–May be fatal if swallowed and enters airways
- H400–Very toxic to aquatic life
- H411–Toxic to aquatic life with long lasting effects

Precautionary statements

Prevention

- Obtain, read and follow all safety instructions before use.
- Avoid release to the environment.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Ground and bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Use non-sparking tools.
- Take action to prevent static discharges.
- Do not breathe vapors.
- Use only outdoors or in a well-ventilated area.
- Wash hands thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- Wash hands thoroughly after handling. Do not touch eyes.
- Do not eat, drink or smoke when using this product.

Response

- In case of fire: Use foam, dry powder, CO2 to extinguish.
- Collect spillage.
- Get medical help.
- IF exposed or concerned, get medical advice.
- Get medical help if you feel unwell.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water or shower.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical help.
- Do NOT induce vomiting.
- IF SWALLOWED: Get emergency medical help immediately.

Storage

- Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Store locked up.

Disposal

- Dispose of contents/container in accordance with local/regional/national/international regulations.

Specific danger/hazard

Physical and Chemical hazards

Highly flammable liquid. Vapor/air mixture may explode.

Section 3. Composition/information on ingredients

Substance/mixture:

Substance

Ingredient name: Ethylbenzene

Content (%): 98.0

Chemical formula: C₈H₁₀

ENCS: 3-28; 3-60

CAS No.: 100-41-4

MW: 106.17

EC No.: 202-849-4

Note : The figures shown above are not the specifications of the product.

Section 4. First aid measures

Descriptions of first aid measures

General measures

Get medical help.

IF exposed or concerned, get medical advice.

Keep victim warm and quiet.

Call emergency medical service.

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

IF INHALED

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

IF INHALED: Get medical help.

IF ON SKIN

IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes.

Gently wash with plenty of soap and water.

In case of burns, immediately cool affected skin for as long as possible with cold water.

Do not remove clothing if adhering to skin.

If skin irritation or rash occurs: Get medical help.

Remove and isolate contaminated clothing and shoes.

IF IN EYES

IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical help.

IF SWALLOWED

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF SWALLOWED: Get emergency medical help immediately.

Most important symptoms and effects, both acute and delayed

(Symptoms when inhalation or ingestion)

Cough. Sore throat. Dizziness. Drowsiness. Headache. Burning sensation in the throat and chest.

(Symptoms when skin and/or eye contact)

Redness. Pain of the eyes.

Indication of any immediate medical attention and special treatment needed

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

In case of fire, use foam, dry powder, CO2 to extinguish.

Unsuitable extinguishing media

Unsuitable extinguishing media data is not available.

Specific hazards arising from the substance or mixture

Containers may explode when heated.

Fire may produce irritating, corrosive and/or toxic gases.

Runoff from fire control or dilution water may cause pollution.

Advice for firefighters

Special extinguishing method

Evacuate non-essential personnel to safe area.

Cool container with water spray.

Special protective equipment and precautions for fire-fighters

Wear fire resistant or flame retardant clothing.

Wear protective gloves/protective clothing/eye protection/face protection.

Firefighters should wear self-contained breathing apparatus with a full facepiece operated in the positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unauthorized personnel away.

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

Ventilate area until material pick up is complete.

Wear proper protective equipment.

PUBLIC SAFETY: Ventilate closed spaces before entering.

Do not touch or walk through spilled material.

Environmental precautions

Runoff to sewer may create fire or explosion hazard.

Vapor explosion hazard indoors, outdoors or in sewers.

Avoid release to headsprings, rivers, lakes, ocean and groundwater.

Methods and materials for containment and cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use clean non-sparking tools to collect absorbed material.

All equipment used when handling the product must be grounded.

Collect leaking and spilled liquid in covered containers as far as possible.

Preventive measures for secondary accident

Collect spillage.

Stop leak if you can do it without risk.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Prevent entry into waterways, sewers, basements or confined areas.

Keep out of low areas.

Reference to other sections

Refer to section 8

Refer to section 13

Section 7. Handling and storage

Engineering measures

(Measures to prevent operator exposure)

Do not breathe vapors.

(Measures to prevent fire and explosion)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

(Local ventilation/general ventilation)

Exhaust/ventilator should be available.

(Precautions)

Avoid contact with skin.

Avoid contact with eyes.

Advice on safe handling

Obtain, read and follow all safety instructions before use.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Use personal protective equipment as required.

When using do not eat, drink or smoke.

Avoidance of contact

See Section 10: Stability and Reactivity.

Advice on general occupational hygiene

Do not get in eyes, on skin, or on clothing.

Wash hands thoroughly after handling. Do not touch eyes.

Do not eat, drink or smoke when using this product.

Conditions for safe storage

Keep container tightly closed. Keep cool.

Store in accordance with local/regional/national/international regulations regulation.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Incompatible substances

Refer to Section 10. Stability and reactivity.

Container and packaging materials for safe handling data is not available.

Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See

Section 8 for exposure controls and personal protection recommendations.

Section 8. Exposure controls/personal protection

Permissible concentration

Control value and Concentration standard value under ISHA

Japan control value 20ppm

Occupational exposure limit values

JSOH

20ppm; 87mg/m³ (skin)

ACGIH

TWA: 20ppm (URT & eye irr; ototoxicity; kidney eff; CNS impair)

Notation

OTO

Exposure controls

Appropriate engineering controls

Do not use in areas without adequate ventilation.

Eye wash station should be available.

Washing facilities should be available.

Individual protection measures, such as personal protective equipment

Respiratory protection

Select and wear respiratory protection in accordance with approved standards (e.g. JIS T8150).

Recommended respiratory protection: Gas mask

Hand protection

Wear protective gloves. Recommended material(s): viton

Inspect before use and replace worn or damaged gloves.

Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions.

Chemical-resistant, impervious gloves complying with an approved standard (e.g. JIS T8116) should be used.

Eye/face protection

Wear safety glasses with side-shields.

Wear eye/face protection in accordance with approved standards (e.g. JIS T8147).

Skin and body protection

Wear impervious clothing and boots in case of repeated or prolonged treatment.

Personal protective equipment for the body and skin should be selected based on the task being performed and the risks involved.

Section 9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical state: Liquid

Color: Colorless

Odor: Aromatic odor

Odor threshold data is not available.

Melting point/Freezing point: -95°C

Boiling point or initial boiling point and boiling range: 136°C

Flammability: Ignitable

Lower and upper explosion limit:

Lower explosion limit: 1.0 vol %

Upper explosion limit: 6.7 vol %

Flash point: 21°C(C.C.)

Auto-ignition temperature: 432°C

Decomposition temperature data is not available.

Self-Accelerating Decomposition Temperature/SADT data is not available.

pH data is not available.

Dynamic viscosity: 0.64mPa·s(25°C)

Kinematic viscosity: 0.63mm²/s(40°C)

Solubility:

Solubility in water: 0.015g/100 mL (20°C)

Solubility in solvent: Miscible with ethanol and diethyl ether.

Partition coefficient n-octanol/water (log value): 3.1

Vapor pressure: 0.9 kPa (20°C)

Vapor density data is not available.

Density and/or relative density: 0.865~0.870 g/mL (20°C)

Relative vapor density (Air=1): 3.7

Relative density of the Vapor/air - mixture at 20°C (Air = 1): 1.02

Particle characteristics data is not available.

Other information

Critical temperature data is not available.

Evaporation rate data is not available.

VOC data is not available.

Section 10. Stability and Reactivity

Reactivity

Reactivity data is not available.

Chemical stability

Stable under normal storage/handling conditions.

Highly flammable.

Possibility of hazardous reactions

The vapour mixes well with air, explosive mixtures are easily formed.

Reacts with strong oxidants.

Attacks plastics and rubber.

Conditions to avoid

Avoid direct sunlight, fire, flame, high temperature.

Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Carbon oxides.

Section 11. Toxicological Information

Information on toxicological effects

Acute toxicity

Acute toxicity (Oral)

[Product]

Based on available data, the classification criteria are not met.

[Data for components of the product]

[NITE-CHRIP]

rat LD50: 3500 – 4700 mg/kg (source: NITE)

Acute toxicity (Dermal)

[Product]

Based on available data, the classification criteria are not met.

[Data for components of the product]

[NITE-CHRIP]

rabbit LD50: 15400 mg/kg (source: NITE)

Acute toxicity (Inhalation)

[Product]

Category 4, Harmful if inhaled

[Data for components of the product]

[NITE-CHRIP]

vapor: rat LC50: 4000 ppm (4-hour) (source: NITE)

mist: rat LC50: 55 mg/L (2-hour) (converted 4-hour equivalent value: 27.5 mg/L) (source: NITE)

Skin corrosion/irritation

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Serious eye damage/irritation

[Product]

Category 2B, Causes eye irritation

[Data for components of the product]

[NITE-CHRIP]

Category 2B (source: NITE)

Respiratory or skin sensitization

Respiratory sensitization

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Skin sensitization

[Product]

Based on available data, the classification criteria are not met.

[Data for components of the product]

[NITE-CHRIP]

Not classified (source: NITE)

Germ cell mutagenicity

[Product]

Based on available data, the classification criteria are not met.

[Data for components of the product]

[NITE-CHRIP]

Not classified (source: NITE)

Carcinogenicity

[Product]

Category 2, Suspected of causing cancer

[Data for components of the product]

[NITE-CHRIP]

Category 2 (source: NITE)

[IARC]

Group 2B : Possibly carcinogenic to humans

[ACGIH]

A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans

[JSOH]

Group 2B: The agents which are probably or possibly carcinogenic to humans

[EPA]

Group D; Not classifiable as to human carcinogenicity(1986)

Reproductive toxicity

[Product]

Category 1B, May damage fertility or the unborn child

[Data for components of the product]

[NITE-CHRIP]

Category 1B (source: NITE)

Specific target organ toxicity – single exposure

[Product]

Category 3, May cause respiratory irritation

Category 3, May cause drowsiness or dizziness

[Data for components of the product]

[NITE-CHRIP]

Category 3 (Respiratory tract irritation), Category 3 (Narcotic effects) (source: NITE)

Specific target organ toxicity – repeated exposure

[Product]

Category 1, Causes damage to organs through prolonged or repeated exposure

[Data for components of the product]

[NITE-CHRIP]

Category 1 (auditory organ, nervous system) (source: NITE)

Aspiration hazard

[Product]

Category 1, May be fatal if swallowed and enters airways

[Data for components of the product]

[NITE-CHRIP]

Category 1 (source: NITE)

Section 12. Ecological Information

Ecotoxicity

Aquatic toxicity

[Product]

Category 1, Very toxic to aquatic life

Category 2, Toxic to aquatic life with long lasting effects

[Data for components of the product]

Hazardous to the aquatic environment, short-term (acute)

[NITE-CHRIP]

Crustacea (*Crangon franciscorum*) 96-hour LC50: 0.42 mg/L (source: NITE)

Fish (*Morone saxatilis*) 96-hour LC50: 3.7 mg/L (source: NITE)

Hazardous to the aquatic environment, long-term (chronic)

[NITE-CHRIP]

Crustacea (*Ceriodaphnia dubia*) 7-day NOEC: 0.956 mg/L (source: NITE)

Water solubility

[Data for components of the product]

0.015 g/100 mL (20°C) (source: ICSC, 2007)

Persistence and degradability

[Data for components of the product]

Not rapidly degradable (Degradation rate: 0% (by BOD)) (source: NITE)

Bioaccumulative potential

[Data for components of the product]

log Pow: 3.1 (source: ICSC, 2007)

Mobility in soil

Mobility in soil data is not available.

Other adverse effects

Ozone depleting chemical data is not available.

Section 13. Disposal considerations

Waste treatment methods

Waste from residues

Disposal should be in accordance with local, national, and international laws and regulations.

Comply with relevant laws and regulations as well as local municipal standards.

Avoid release to the environment.

Do not dump into sewers, on the ground or into any body of water.

Contaminated packing

Disposal should be in accordance with local, national, and international laws and regulations.

Comply with relevant laws and regulations as well as local municipal standards.

Dispose of container after using the contents completely.

Section 14. Transport Information

UNRTDG

Ethylbenzene, JUNSEI CHEMICAL CO., LTD., 17285jis_J_E2-3, 21/Apr/2026

UN number : UN1175

UN Proper Shipping Name : ETHYLBENZENE

Transport hazard class(es) : 3

Packing group : II

IMDG Code (International Maritime Dangerous Goods Regulations)

UN number : UN1175

UN Proper Shipping Name : ETHYLBENZENE

Transport hazard class(es) : 3

Packing group : II

IATA (Dangerous Goods Regulations)

UN number : UN1175

UN Proper Shipping Name : ETHYLBENZENE

Transport hazard class(es) : 3

Hazard labels : Flamm. liquid

Packing group : II

Environmental hazards

Marine pollutants (yes/no) : no

Environmentally hazardous substance/mixture (yes/no) : yes

Maritime transport in bulk according to IMO instruments**MARPOL Annex II – Noxious Liquid Substances**

Noxious Liquid Substances ; Cat. Y

Ethylbenzene

Flammable Liquid

Ethylbenzene

MARPOL Annex V – HME (Harmful to the Marine Environment)

Reproductive toxicity: cat.1, 1A, 1B

Ethylbenzene

Specific target organ toxicity – repeated exposure: cat.1

Ethylbenzene

Hazardous to the aquatic environment – short-term (acute): cat.1

Ethylbenzene

Hazardous to the aquatic environment – long-term (chronic): cat.1, 2

Ethylbenzene

ERG GUIDE No.: 130

Section 15. Regulatory Information**U.S. Toxic Substances Control Act (TSCA) Inventory**

Chemicals listed in TSCA Inventory

100-41-4

All components are listed or exempted.

Superfund Amendments and Reauthorizations Act (SARA), Title III

SARA 313 (TRI)

Ethylbenzene

Other regulatory information

We are not able to check up the regulatory information with regard to the substances in your country or region, therefore, we request this matter would be filled by your responsibility.

Regulatory information with regard to this substance in your country or in your region should be examined by your own responsibility.

Ethylbenzene, JUNSEI CHEMICAL CO., LTD., 17285jis_J_E2-3, 21/Apr/2026

Ensure this material in compliance with federal requirements and ensure conformity to local regulations.
Regulatory information in this section are limited to intentional ingredient(s), but does not contain information on non-intentional ingredients or impurities which are not informed by supplier(s).

Chemical safety assessment

Advice on safe handling for this product can be found in sections 7 and 8 of this SDS.

Section 16. Other information

GHS classification and labelling

H225-Flammable liquids, Category 2: H225 Highly flammable liquid and vapor
H332-Acute toxicity, Category 4: H332 Harmful if inhaled
H320-Serious eye damage/eye irritation, Category 2B: H320 Causes eye irritation
H351-Carcinogenicity, Category 2: H351 Suspected of causing cancer
H360-Reproductive toxicity, Category 1B: H360 May damage fertility or the unborn child
H335-Specific target organ toxicity – single exposure, Category 3, Respiratory tract irritation: H335 May cause respiratory irritation
H336-Specific target organ toxicity – single exposure, Category 3, Narcotic effects: H336 May cause drowsiness or dizziness
H372-Specific target organ toxicity – Repeated exposure, Category 1: H372 Causes damage to organs through prolonged or repeated exposure
H304-Aspiration hazard, Category 1: H304 May be fatal if swallowed and enters airways
H400-Hazardous to the aquatic environment, short-term (acute), Category 1: H400 Very toxic to aquatic life
H411-Hazardous to the aquatic environment, long-term (chronic), Category 2: H411 Toxic to aquatic life with long lasting effects

References and sources for data

Globally Harmonized System of classification and labelling of chemicals, UN
Recommendations on the TRANSPORT OF DANGEROUS GOODS 23rd edit., 2023 UN
IMDG Code, 2024 Edition (Incorporating Amendment 42-24)
IATA Dangerous Goods Regulations (67th Edition) 2026
2024 EMERGENCY RESPONSE GUIDEBOOK (US DOT)
2026 TLVs and BEIs. (ACGIH)
JIS Z 7252 : 2025
JIS Z 7253 : 2025
Recommendation of occupational exposure limits (2024-2025) (JSOH)
Notification No. 0111-1 (January 11, 2022), Chemical Hazards Control Division, Industrial
Safety and Health Department, Labour Standards Bureau, MHLW in Japan
Supplier's data/information
Chemicals safety data management system "GHS Assistant" Version 4.38
(<https://www.asahi-ghs.com/>)
NITE Chemical Risk Information Platform "NITE-CHRIP"
(https://www.chem-info.nite.go.jp/en/chem/chrip/chrip_search/systemTop)
GHS Classification Guidance for Enterprises 2019 Revised Edition (Ver. 2.1) (May. 2024, METI)

Abbreviations and acronyms

ACGIH – American Conference of Governmental Industrial Hygienists;
anh – anhydride;
ATE – Acute Toxicity Estimate;

BCF – Bioconcentration Factor;
BOD – Biochemical Oxygen Demand;
Cat. – Category;
Ceiling-C – Ceiling value;
COD – Chemical Oxygen Demand;
CSCL – Chemical Substances Control Law in Japan;
DSEN – Dermal Sensitization;
EC No. – The European Community number;
EC50 – Effective Concentration 50;
ENCS – Existing and New Chemical Substances Inventory under CSCL
EPA – US Environmental Protection Agency;
EU – European Union;
GHS – Globally Harmonized System of Classification and Labelling of Chemicals;
IARC – International Agency for Research on Cancer;
IATA – International Air Transport Association;
IBC Code – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk;
IMDG Code – International Maritime Dangerous Goods Code;
ISHA – Industrial Safety and Health Act in Japan;
JSOH – Japan Society for Occupational Health;
LC50 – Lethal Concentration 50;
LD50 – Lethal Dose 50;
logPow – n-Octanol/water Partition Coefficient;
MARPOL – International Convention for the Prevention of Pollution from Ships;
METI – Ministry of Economy, Trade and Industry in Japan;
MHLW – Ministry of Health, Labour and Welfare in Japan;
MOE – Ministry of the Environment in Japan
NOEC – No Observed Effect Concentration;
NTP – US National Toxicology Program;
REACH – Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No.1907/2006;
RSEN – Respiratory Sensitization;
Skin – Danger of cutaneous absorption;
STEL – Short-term Exposure Limit;
STOT – Specific target organ toxicity;
SVHC – Substance of Very High Concern under REACH;
TWA – time-weighted average;
UN – United Nations;
UNRTDG – United Nations Recommendations on the Transport of Dangerous Goods;

General Disclaimer

The information relates to this specific material. It may not be valid for this material, if used in combination with any other materials or in any process. It is the user's responsibility to satisfy him-selves as to the suitability and completeness of this information for his own particular use.

This data sheet was created based on the information we currently have and may be revised according to new information. In addition, the precautions apply only to normal handling, and in the case of special handling, please make adequate countermeasure to maintain your safety. The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The

Ethylbenzene, JUNSEI CHEMICAL CO., LTD., 17285jis_J_E2-3, 21/Apr/2026

data does not signify any warranty with regard to the products' properties.

The GHS classification data given here is based on current Data published in Japan
(National Institute of Technology and Evaluation (NITE) Chemical Risk Information Platform
(NITE-CHRIP), up to FY2024).