

Safety Data Sheet

Section 1. Identification of the substance/mixture and of the company/undertaking

Product identifier:

Product name: p-Xylene

Reference number(SDS):25180jis_J_E1-3

Product type:

Reagent

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the product: Research and Development

Uses advised against: Do not use for other purposes.

Details of the supplier of the safety data sheet

Manufacturer/Supplier: JUNSEI CHEMICAL CO., LTD.

Address: 1-6, Ohmano-cho, Koshigaya-shi, Saitama 343-0844, Japan

Division: Quality Assurance Department

Telephone number: +81-48-986-6161

FAX: +81-48-989-2787

e-mail address: shiyaku-t@junsei.co.jp

Section 2. Hazards identification

GHS classification and label elements of the product

Classification of the substance or mixture

PHYSICAL AND CHEMICAL HAZARDS

Flammable liquids: Category 3

HEALTH HAZARDS

Acute toxicity (Inhalation): Category 4

Skin corrosion/irritation: Category 2

Reproductive toxicity: Category 2

Specific target organ toxicity – single exposure: Category 1 (central nervous system)

Specific target organ toxicity – single exposure: Category 3 (Respiratory tract irritation)

Specific target organ toxicity – single exposure: Category 3 (Narcotic effects)

Aspiration hazard: Category 1

ENVIRONMENT HAZARDS

Hazardous to the aquatic environment, short-term (acute): Category 2

Hazardous to the aquatic environment, long-term (chronic): Category 2

(Note) GHS classification without description: Not classified/Classification not possible

Label elements



Signal word: Danger

HAZARD STATEMENT

H226-Flammable liquid and vapor

H332-Harmful if inhaled

H315-Causes skin irritation

H361-Suspected of damaging fertility or the unborn child

H370-Causes damage to organs

H335-May cause respiratory irritation

H336-May cause drowsiness or dizziness

p-Xylene ,JUNSEI CHEMICAL CO., LTD.,25180jis_J_E1-3,10/Jul/2024

H304–May be fatal if swallowed and enters airways

H401–Toxic to aquatic life

H411–Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENT**Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid release to the environment.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Do not breathe vapors.

Use only outdoors or in a well-ventilated area.

Wash contaminated parts thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Do not eat, drink or smoke when using this product.

Response

In case of fire: Use water mist, foam, dry powder, CO2 to extinguish.

Collect spillage.

IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER/doctor/physician if you feel unwell.

IF exposed or concerned: Call a POISON CENTER/doctor/physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Do NOT induce vomiting.

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Disposal

Dispose of contents/container in accordance with local/national regulation.

Specific Physical and Chemical hazards

Flammable liquid. Vapor/air mixture may explode.

Section 3. Composition/information on ingredients**Mixture/Substance selection:****Substance**

Common name, synonyms: 1,4-Dimethylbenzene

Ingredient name:p-Xylene

Content (%):100

Chemical formula:C8H10

Chemicals No, Japan:3-3;3-60

CAS No.:106-42-3

MW:106.17

EC No.:203-396-5

Note : The figures shown above are not the specifications of the product.

Section 4. First-aid measures

Descriptions of first-aid measures

General measures

- IF exposed or concerned: Get medical advice/attention.
- Call a POISON CENTER/doctor/physician if you feel unwell.
- Keep victim warm and quiet.
- Call emergency medical service.
- Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

IF INHALED

- Remove person to fresh air and keep comfortable for breathing.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Call a POISON CENTER/doctor/physician if you feel unwell.

IF ON SKIN (or hair)

- Take off immediately all contaminated clothing. Rinse skin with water or shower.
- Wash with plenty of soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water.
- Do not remove clothing if adhering to skin.
- If skin irritation or rash occurs: Get medical advice/attention.
- If skin irritation occurs: Get medical advice/attention.
- Remove and isolate contaminated clothing and shoes.

IF IN EYES

- Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

IF SWALLOWED

- Rinse mouth. Do NOT induce vomiting.
- Immediately call a POISON CENTER/doctor/physician.
- Call a POISON CENTER/doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

(Symptoms when inhalation or ingestion)

- Dizziness. Drowsiness. Headache. Nausea. Burning sensation. Abdominal pain.

(Symptoms when skin and/or eye contact)

- Dry skin. Conjunctival redness of the eyes. Redness of the skin. Pain of the eyes.

Indication of any immediate medical attention and special treatment needed

- Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

- In case of fire, use water mist, foam, dry powder, CO2 to extinguish.

Unsuitable extinguishing media

- Unsuitable extinguishing media data is not available.

Specific hazards arising from the substance or mixture

- Containers may explode when heated.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control or dilution water may cause pollution.

Advice for firefighters**Specific fire-fighting measures**

- Evacuate non-essential personnel to safe area.
- Cool container with water spray.

Special protective equipment and precautions for fire-fighters

- Wear fire resistant or flame retardant clothing.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Firefighters should wear self-contained breathing apparatus with a full facepiece operated in the positive pressure mode.

Section 6. Accidental release measures**Personnel precautions, protective equipment and emergency procedures**

- Evacuate area.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Ventilate area until material pick up is complete.
- Wear proper protective equipment.
- PUBLIC SAFETY:** Ventilate closed spaces before entering.
- Do not touch or walk through spilled material.

Environmental precautions

- Runoff to sewer may create fire or explosion hazard.
- Vapors may form explosive mixtures with air.
- Avoid release to headsprings, rivers, lakes, ocean and groundwater.

Methods and materials for containment and cleaning up

- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Use clean non-sparking tools to collect absorbed material.
- All equipment used when handling the product must be grounded.

Preventive measures for secondary accident

- Collect spillage.
- Stop leak if you can do it without risk.
- ELIMINATE** all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Prevent entry into waterways, sewers, basements or confined areas.
- Keep out of low areas.

Section 7. Handling and storage**Precautions for safe handling****Preventive measures****(Exposure Control for handling personnel)**

- Do not breathe vapors.

(Protective measures against fire and explosion)

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Ground and bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Use non-sparking tools.
- Take action to prevent static discharges.

(Exhaust/ventilator)

- Exhaust/ventilator should be available.

(Safety treatments)

- Avoid contact with skin.
- Avoid contact with eyes.

Safety Measures

- Obtain special instructions before use.

p-Xylene ,JUNSEI CHEMICAL CO., LTD.,25180jis_J_E1-3,10/Jul/2024

Do not handle until all safety precautions have been read and understood.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

When using do not eat, drink or smoke.

Any incompatibilities

Strong acids, Strong oxidizing agents should not be mixed with the chemicals.

Advice on general occupational hygiene

Wash contaminated parts thoroughly after handling.

Do not eat, drink or smoke when using this product.

Take off contaminated clothing and wash it before reuse.

Storage

Conditions for safe storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Protect from sunlight.

Store in accordance with local/national regulation.

Store locked up.

Container and packaging materials for safe handling

Keep only in original packaging.

Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See

Section 8 for exposure controls and personal protection recommendations.

Section 8. Exposure controls/personal protection

Control parameters

Control value and Concentration standard value

Japan control value 50ppm

Adopted value

JSOH(2001) 50ppm; 217mg/m³

ACGIH(2021) TWA: 20ppm (Eye & URT irr; hematologic eff; ototoxicity; CNS impair)

[ACGIH] Notation

OTO

Exposure controls

Appropriate engineering controls

Do not use in areas without adequate ventilation.

Eye wash station should be available.

Washing facilities should be available.

Individual protection measures

Respiratory protection

Select and wear respiratory protection in accordance with approved standards (e.g. JIS T8150).

Recommended respiratory protection: Gas mask

Hand protection

Wear protective gloves. Recommended material(s): viton

Inspect before use and replace worn or damaged gloves.

Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions.

Chemical-resistant, impervious gloves complying with an approved standard (e.g. JIS T8116) should be used.

Eye protection

Wear safety glasses with side-shields.

Wear eye/face protection in accordance with approved standards (e.g. JIS T8147).

Skin and body protection

Wear impervious clothing and boots in case of repeated or prolonged treatment.

Personal protective equipment for the body and skin should be selected based on the task being performed and the risks involved.

Section 9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical state: Liquid

Color: Colorless

Odor: Characteristic odor

Odor threshold: 0.05ppm

Melting point/Freezing point: 13°C

Boiling point or initial boiling point: 138°C

Boiling range data is not available.

Flammability (gases, liquids and solids): Ignitable

Lower and upper explosion limit/flammability limit:

Lower explosion limit: 1.1 vol %

Upper explosion limit: 7.0 vol %

Flash point: (c.c.)27°C

Auto-ignition temperature: 528°C

Decomposition temperature data is not available.

Self-Accelerating Decomposition Temperature/SADT data is not available.

pH data is not available.

Dynamic viscosity: 0.603mPas(25°C)

Kinematic viscosity: 0.70mm²/s(25/20°C)

Solubility:

Solubility in water: 0.162(25°C)

Solubility in solvent: Miscible in acetone, alcohol, ether, benzene.

n-Octanol/water partition coefficient: log Pow3.15

Vapor pressure: 0.9 kPa (20°C)

Density and/or relative density: 0.859~0.868 g/ml (20°C)

Relative vapor density (Air=1): 3.7

Relative density of the Vapor/air - mixture at 20°C (Air = 1): 1.02

Particle characteristics data is not available.

Other information

Critical temperature data is not available.

Evaporation rate data is not available.

VOC data is not available.

Section 10. Stability and Reactivity

Reactivity

Runaway polymerization will not occur.

Chemical stability

Stable under normal storage/handling conditions.

Flammable.

Possibility of hazardous reactions

As a result of flow, agitation, etc., electrostatic charges can be generated.

Reacts with strong acids and strong oxidants.

Conditions to avoid

Contact with incompatible materials.

Open flames. Heating. Sparks.

Incompatible materials

Strong acids, Strong oxidizing agents

Hazardous decomposition products
Carbon oxides

Section 11. Toxicological Information

Information on toxicological effects

Acute toxicity

Acute toxicity (Oral)

[Product]

Based on available data, the classification criteria are not met.

[Data for components of the product]

[GHS Cat. Japan, base data]

rat LD50=4029mg/kg (EHC 190 1997)

Acute toxicity (Dermal)

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Acute toxicity (Inhalation)

[Product]

Category 4, Harmful if inhaled

[Data for components of the product]

[GHS Cat. Japan, base data]

vapor: rat LC50=4740ppm/4hr (EHC 190, 1997)

Irritant properties

Skin corrosion/irritation

[Product]

Category 2, Causes skin irritation

[Data for components of the product]

[GHS Cat. Japan, base data]

rabbit : skin irritation (EHC 190, 1997)

Serious eye damage/irritation

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Sensitization

Respiratory sensitization

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Skin sensitization

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Germ cell mutagenicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Carcinogenicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

[ACGIH]

A4(2021) : Not Classifiable as a Human Carcinogen

[EPA]

I; Inadequate information to assess carcinogenic potential(2005)

Reproductive toxicity

[Product]

Category 2, Suspected of damaging fertility or the unborn child

[Data for components of the product]

[GHS Cat. Japan, base data]

cat. 2; ATSDR, 2007

Specific target organ toxicity (STOT)

STOT-single exposure

[Product]

Category 1, Causes damage to organs

Category 3, May cause respiratory irritation

Category 3, May cause drowsiness or dizziness

[Data for components of the product]

[cat.1]

[GHS Cat. Japan, base data]

central nervous system (CERI/NITE Hazard Assessment Report, 2008)

[cat.3 (respiratory tract irritation)]

[GHS Cat. Japan, base data]

respiratory tract irritation (ACGIH 7th, 2001)

[cat.3 (narcotic effects)]

[GHS Cat. Japan, base data]

narcotic effect (CERI/NITE Hazard Assessment Report, 2008)

STOT-repeated exposure

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Aspiration hazard

[Product]

Category 1, May be fatal if swallowed and enters airways

[Data for components of the product]

[cat.1]

[GHS Cat. Japan, base data]

cat. 1; hydrocarbon, kinematic viscosity=0.70 mm²/s (25°C) (HSDB, Access on August 2015 calc.)

Section 12. Ecological Information

Toxicity

Aquatic toxicity

[Product]

Category 2, Toxic to aquatic life

Category 2, Toxic to aquatic life with long lasting effects

[Data for components of the product]

Hazardous to the aquatic environment, short-term (acute)

[GHS Cat. Japan, base data]

Crustacea (Crangon franciscorum) LC50=1.7mg/L/96hr (NITE Initial Risk Assessment Report, 2005)

Water solubility

[Data for components of the product]

0.162g/L(25°C) (HSDB)

Persistence and degradability

[Data for components of the product]

Not rapidly degradable [BOD=38% (MITI official bulletin, 1975)]

Bioaccumulative potential

[Data for components of the product]

log Pow=3.15 (PHYSPROP DB, 2005)

Mobility in soil

Mobility in soil data is not available.

Other adverse effects

Ozone depleting chemical data is not available.

Section 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Waste treatment methods

Avoid release to the environment.

Dispose of contents/container in accordance with local/national regulation.

Section 14. Transport Information

UN No., UN CLASS

UN Number or ID Number : 1307

UN Proper Shipping Name : XYLENES

Class or division (Transport hazard class) : 3

Packing group : III

ERG GUIDE No.: 130

IMDG Code (International Maritime Dangerous Goods Regulations)

UN Number or ID Number : 1307

UN Proper Shipping Name : XYLENES

Class or division (Transport hazard class) : 3

Packing group : III

IATA (Dangerous Goods Regulations)

UN Number or ID Number : 1307

UN Proper Shipping Name : XYLENES

Class or division (Transport hazard class) : 3

Hazard labels : Flamm.liquid

Packing group : III

Environmental hazards

Marine pollutants (yes/no) : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Noxious Liquid Substances ; Cat. Y

p-Xylene

Flammable Liquid

p-Xylene

MARPOL Annex V – HME (Harmful to the Marine Environment)

Hazardous to the aquatic environment – long-term (chronic): cat.1, 2

p-Xylene

Section 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Labor Standards Act, Japan

Chemical substances or compounds (including alloys) causing disease (Regulation, Appended Table1-2-4-1)

p-Xylene

U.S. Toxic Substances Control Act (TSCA) Inventory

Chemicals listed in TSCA Inventory

106-42-3

All components are listed or exempted.

Superfund Amendments and Reauthorizations Act (SARA), Title III

SARA 313 (TRI)

p-Xylene

Other regulatory information

We are not able to check up the regulatory information with regard to the substances in your country or region, therefore, we request this matter would be filled by your responsibility.

Regulatory information with regard to this substance in your country or in your region should be examined by your own responsibility.

Ensure this material in compliance with federal requirements and ensure conformity to local regulations.

Regulatory information in this section are limited to intentional ingredient(s), but does not contain information on non-intentional ingredients or impurities which are not informed by supplier(s).

Chemical safety assessment

Advice on safe handling for this product can be found in sections 7 and 8 of this SDS.

Section 16. Other information

GHS classification and labelling

H226-Flammable liquids, Category 3: H226 Flammable liquid and vapour

H332-Acute toxicity, Category 4: H332 Harmful if inhaled

H315-Skin corrosion/irritation, Category 2: H315 Causes skin irritation

H361-Reproductive toxicity, Category 2: H361 Suspected of damaging fertility or the unborn child

H370-STOT – single exposure, Category 1: H370 Causes damage to organs

H335-STOT – single exposure, Category 3, Respiratory tract irritation: H335 May cause respiratory irritation.

H336-STOT – single exposure, Category 3, Narcotic effects: H336 May cause drowsiness or dizziness.

H304-Aspiration hazard, Category 1: H304 May be fatal if swallowed and enters airways

H401-Hazardous to the aquatic environment, short-term (acute), Category 2: H401 Toxic to aquatic life

H411-Hazardous to the aquatic environment, long-term (chronic), Category 2: H411 Toxic to aquatic life with long lasting effects

References and sources for data

Globally Harmonized System of classification and labelling of chemicals, UN

Recommendations on the TRANSPORT OF DANGEROUS GOODS 22nd edit., 2021 UN

IMDG Code, 2022 Edition (Incorporating Amendment 41-22)

IATA Dangerous Goods Regulations (65th Edition) 2024

2020 EMERGENCY RESPONSE GUIDEBOOK (US DOT)

2024 TLVs and BEIs. (ACGIH)

JIS Z 7252 : 2019

JIS Z 7253 : 2019

2023 Recommendation on TLVs (JSOH)

Notification No. 0111-1 (January 11, 2022), Chemical Hazards Control Division, Industrial Safety and Health Department, Labour Standards Bureau, MHLW in Japan

Supplier's data/information

Chemicals safety data management system "GHS Assistant" Version 4.29 (<https://www.asahi-ghs.com/>)

NITE Chemical Risk Information Platform "NITE-CHRIIP"

(https://www.chem-info.nite.go.jp/chem/chrip/chrip_search/systemTop)

GHS Classification Guidance for Enterprises 2019 Revised Edition (Ver. 2.1) (May. 2024, METI)

Abbreviations and acronyms

SDS (Safety Data Sheet)

LD50 (Lethal Dose, 50%)

LC50 (Lethal Concentration, 50%)

IARC (International Agency for Research on Cancer)

ACGIH (American Conference of Governmental Industrial Hygienists)

EPA (US Environmental Protection Agency)

NTP (US National Toxicology Program)

METI (Ministry of Economy, Trade and Industry in Japan)

MHLW (Ministry of Health, Labour and Welfare in Japan)

MOE (Ministry of the Environment in Japan)

JSOH (Japan Society for Occupational Health)

ISHA (Industrial Safety and Health Act in Japan)

CSCL (Chemical Substances Control Law in Japan)

EU (European Union)

EC50 (Effective Concentration, 50%)

NOEC (No Observed Effect Concentration)

BOD (Biochemical Oxygen Demand)

COD (Chemical Oxygen Demand)

BCF (Bioconcentration Factor)

anh (anhydride)

General Disclaimer

This data sheet was created based on the information we currently have and may be revised according to new information. In addition, the precautions apply only to normal handling, and in the case of special handling, please make adequate countermeasure to maintain your safety.

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the products' properties.

The GHS classification data given here is based on current Japan official data (NITE published in 2022).