

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

Product identifier:

Product name: Chromium(III) nitrate solution 40%

Product code(SDS NO): 37420jis_J_E1-1

Details of the supplier of the safety data sheet

Manufacturer/Supplier: JUNSEI CHEMICAL CO., LTD.

Address: 1-6, Ohmano-Cho, Koshigaya, Saitama 343-0844, Japan

Division: Quality Assurance Department

Telephone number: +81-48-986-6161

FAX: +81-48-989-2787

e-mail address: shiyaku-t@junsei.co.jp

2. Hazards identification

GHS classification and label elements of the product

Classification of the substance or mixture

Physiocal and chemical hazards

Oxidizing liquids: Category 3

HEALTH HAZARDS

Respiratory sensitization: Category 1

Skin sensitization: Category 1

(Note) GHS classification without description: Not applicable/Out of classification/Not classifiable

Label elements



Signal word: Danger

HAZARD STATEMENT

May intensify fire; oxidizer

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

PRECAUTIONARY STATEMENT

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep/Store away from clothing/combustible materials.

Take any precaution to avoid mixing with combustibles and/or other incompatible materials.

Avoid breathing dust/fume/gas/mist/vapors/spray.

In case of inadequate ventilation wear respiratory protection. (as specified by the manufacturer/supplier or the competent authority.)

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves and face protection.

Response

In case of fire: Use appropriate media for extinction.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Chromium(III) nitrate solution 40%,
JUNSEI CHEMICAL CO., LTD., 37420jis_J_E1-1, 19/03/2018

Disposal

Dispose of contents/container in accordance with local/national regulation.

Physical and Chemical hazards

Oxidizing material. Organic or combustible material may catch fire in contact with it.

3. Composition/information on ingredients

Mixture/Substance selection:

Mixture

Ingredient name: Chromium (III) nitrate

Content(%): 40 <

Chemical formula: CrN_3O_9

Chemicals No, Japan: 1-281

CAS No.: 13548-38-4

MW: 238.01

ECNO: 236-921-1

Ingredient name: Water

Content(%): Residual quantity of the ingredient mentioned above.

Chemical formula: H_2O

CAS No.: 7732-18-5

MW: 18.02

ECNO: 231-791-2

4. First-aid measures

Descriptions of first-aid measures

IF INHALED

Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN (or hair)

Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF SWALLOWED

Rinse mouth.

Call a POISON CENTER or doctor/physician if you feel unwell.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Use appropriate extinguishing media suitable for surrounding facilities.

The product is non-flammable.

Specific hazards arising from the substance or mixture

Containers may explode when heated.

Fire may produce irritating, corrosive and/or toxic gases.

Runoff from fire control or dilution water may cause pollution.

Advice for firefighters

Specific fire-fighting measures

Evacuate non-essential personnel to safe area.

Special protective equipment and precautions for fire-fighters

Wear fire/ flame resistant/retardant clothing.

Wear protective gloves/protective clothing/eye protection/face protection.

Firefighters should wear self-contained breathing apparatus with full face piece operated positive pressure mode.

6. Accidental release measures

Personnel precautions, protective equipment and emergency procedures

Keep unauthorized personnel away.

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

Ventilate area after material pick up is complete.

Wear proper protective equipment.

PUBLIC SAFETY: Ventilate closed spaces before entering.

Environmental precautions

Avoid release to the rivers, lakes, ocean and groundwater.

Methods and materials for containment and cleaning up

Absorb spill with inert material (dry sand, earth, et al), then place in a chemical waste container.

Preventive measures for secondary accident

Collect spillage.

Stop leak if you can do it without risk.

Keep combustibles (wood, paper, oil, etc.) away from spilled material.

7. Handling and storage

Precautions for safe handling

Preventive measures

(Exposure Control for handling personnel)

Avoid breathing dust/fume/gas/mist/vapors/spray.

(Protective measures against fire and explosion)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep/Store away from clothing/combustible materials.

Exhaust/ventilator

Exhaust/ventilator should be available.

Safety treatments

Avoid contact with skin.

Avoid contact with eyes.

Avoid breathing dust, fume, gas, mist or vapor.

Safety Measures/Incompatibility

Take any precaution to avoid mixing with combustibles/incompatible materials.

Wear protective gloves, protective clothing or face protection.

Wear protective gloves and face protection.

Use personal protective equipment as required.

When using do not eat, drink or smoke.

Conditions for safe storage, including any incompatibilities

Recommendation for storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Protect from sunlight.

8. Exposure controls/personal protection

Control parameters

No control value data available in MHLW

Adopted value

(Chromium (III) nitrate)

JSOH(1989) 0.5mg-Cr(III)/m³

ACGIH(1991) TWA: 0.5mg-inorganic Cr III/m³ (URT & skin irr)

Exposure controls

Appropriate engineering controls

Do not use in areas without adequate ventilation.

Eye wash station should be available.

Washing facilities should be available.

Individual protection measures

Respiratory protection

Wear respiratory protection.

Hand protection

Wear protective gloves. Recommended material(s): nitrile

Consult with your glove and/or personnel equipment manufacturer for selection of appropriate compatible materials.

Eye protection

Wear safety glasses with side-shields.

Wear eye/face protection.

Safety and Health measures

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash it before reuse.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical properties

Appearance: Liquid

Color: Indigo blue

Odor data N.A.

pH data N.A.

Phase change temperature

Initial Boiling Point/Boiling point data N.A.

Melting point/Freezing point data N.A.

Decomposition temperature data N.A.

Flash point data N.A.

Auto-ignition temperature data N.A.

Explosive properties data N.A.

Vapor pressure data N.A.

Vapor density data N.A.

Specific gravity/Density data N.A.

Solubility

Solubility in water: Miscible

n-Octanol /water partition coefficient data N.A.

10. Stability and Reactivity

Reactivity

Runaway polymerization will not occur.

Chromium(III) nitrate solution 40%,
JUNSEI CHEMICAL CO., LTD.,37420jis_J_E1-1,19/03/2018

Chemical stability

Stable under normal storage/handling conditions.

Conditions to avoid

Contact with incompatible materials.

Heat.

Incompatible materials

Reducing agents, Combustible substances

Hazardous decomposition products

Nitrogen oxides, Chromic oxides.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Acute toxicity (Oral)

(Chromium(III) nitrate)

rat LD50=3250mg/kg(Environmental Risk Assessment for Chemical Substance by MOE vol.8,2010)

Labor standard law, Japan; Toxic

Chromium (III) nitrate

No Irritant properties data available

Sensitization

Respiratory sensitization

(Chromium(III) nitrate) JSOH-2: probably induce allergic reactions in humans

Skin sensitization

(Chromium(III) nitrate) JSOH-1: induce allergic reactions in humans

No Mutagenic effects data available

Carcinogenicity

(Chromium (III) nitrate)

IARC-Gr.3 : Not Classifiable as a Human Carcinogen

ACGIH-A4(1991) : Not Classifiable as a Human Carcinogen (Inorganic Cr(III))

No reproductive toxicity data available

No STOT-single/repeated exposure data available

No Aspiration hazard data available

Additional data

There are no data available on the preparation itself.

12. Ecological Information

Ecotoxicity

No Aquatic toxicity data available

No Persistence and degradability data available

No Bioaccumulative potential data available

13. Disposal considerations

Waste treatment methods

Dispose of contents/container in accordance with local/national regulation.

14. Transport Information

UN No, UN CLASS

UN number: 3218

UN proper shipping name: NITRATES, INORGANIC, AQUEOUS SOLUTION, N.O.S.

Transport hazard class(es): 5.1

Chromium(III) nitrate solution 40%,
JUNSEI CHEMICAL CO., LTD.,37420jis_J_E1-1,19/03/2018

Packing group: III
ERG GUIDE NO.: 140

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

US major regulations

TSCA

Water; Chromium (III) nitrate

Other regulatory information

We are not able to check up the regulatory information in regard to the substances in your country or region, therefore, we request this matter would be filled by your responsibility.

Regulatory information with regard to this substance in your country or in your region should be examined by your own responsibility.

Ensure this material in compliance with federal requirements and ensure conformity to local regulations.

16. Other information

GHS classification and labelling

Ox. Liq. 3: H272 May intensify fire; oxidizer

Resp. Sens. 1: H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

Skin Sens. 1: H317 May cause an allergic skin reaction

Reference Book

Globally Harmonized System of classification and labelling of chemicals, (5th ed., 2013), UN

Recommendations on the TRANSPORT OF DANGEROUS GOODS 19th edit., 2015 UN

Classification, labelling and packaging of substances and mixtures (table3-1 ECNO6182012)

2016 EMERGENCY RESPONSE GUIDEBOOK (US DOT)

2017 TLVs and BEIs. (ACGIH)

<http://monographs.iarc.fr/ENG/Classification/index.php>

Supplier's data/information

Hazard Communication Standard – 2012

NITE Chemical Risk Information Platform (NITE-CHRIP) <http://www.safe.nite.go.jp/japan/db.html>

GHS Classification Guidance for Enterprises 2013 Revised Edition (August, 2013, METI)

General Disclaimer

This information contained in this data sheet represents the best information currently available to us. However, no warranty is made with respect to its completeness and we assume no liability resulting from its use. It are advised to make their own tests to determinate the safety and suitability of each such product or combination for their own purposes.

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the products' properties.

The GHS classification data given here is based on current Japan official data (NITE published in 2016).