

Safety Data Sheet

Section 1. Identification of the substance/mixture and of the company/undertaking

Product identifier:

Product name: Ethyl methacrylate

Reference number(SDS):73065jis_J_E1-2

Product type:

Reagent

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the product: Research and Development

Uses advised against: Do not use for other purposes.

Details of the supplier of the safety data sheet

Manufacturer/Supplier: JUNSEI CHEMICAL CO., LTD.

Address: 1-6, Ohmano-cho, Koshigaya-shi, Saitama 343-0844, Japan

Division: Quality Assurance Department

Telephone number: +81-48-986-6161

FAX: +81-48-989-2787

e-mail address: shiyaku-t@junsei.co.jp

Section 2. Hazards identification

GHS classification and label elements of the product**Classification of the substance or mixture****PHYSICAL AND CHEMICAL HAZARDS**

Flammable liquids: Category 2

Self-reactive substances and mixtures: Type G

HEALTH HAZARDS

Acute toxicity (Inhalation): Category 4

Skin sensitization: Category 1

Specific target organ toxicity – single exposure: Category 3 (Respiratory tract irritation)

(Note) GHS classification without description: Not classified/Classification not possible

Label elements

Signal word: Danger

HAZARD STATEMENT

H225-Highly flammable liquid and vapor

H332-Harmful if inhaled

H317-May cause an allergic skin reaction

H335-May cause respiratory irritation

PRECAUTIONARY STATEMENT**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Ethyl methacrylate ,JUNSEI CHEMICAL CO., LTD.,73065jis_J_E1-2,01/Sep/2025

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

In case of fire: Use foam, dry powder, CO2 to extinguish.

Call a POISON CENTER/doctor/physician if you feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Disposal

Dispose of contents/container in accordance with local/national regulation.

Specific Physical and Chemical hazards

Highly flammable liquid. Vapor/air mixture may explode.

Section 3. Composition/information on ingredients**Mixture/Substance selection:****Substance**

Ingredient name: Ethyl methacrylate

Content (%): 99.0 <

Chemical formula: C₆H₁₀O₂

ENCS: 2-1039

CAS No.: 97-63-2

MW: 114.14

EC No.: 202-597-5

Impurities

Methyl methacrylate (CAS No.: 80-62-6) : <0.2%

Stabilizing additives

Topanol A (CAS No.: 1879-09-0) : 10ppm

Note : The figures shown above are not the specifications of the product.

Section 4. First-aid measures**Descriptions of first-aid measures****General measures**

Call a POISON CENTER/doctor/physician if you feel unwell.

Keep victim warm and quiet.

Call emergency medical service.

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

IF INHALED

Remove person to fresh air and keep comfortable for breathing.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

Call a POISON CENTER/doctor/physician if you feel unwell.

IF INHALED: Call a POISON CENTER/doctor/physician if you feel unwell.

IF ON SKIN (or hair)

Take off immediately all contaminated clothing. Rinse skin with water or shower.

Wash with plenty of soap and water.

In case of burns, immediately cool affected skin for as long as possible with cold water.

Do not remove clothing if adhering to skin.

If skin irritation or rash occurs: Get medical advice/attention.

Remove and isolate contaminated clothing and shoes.

IF IN EYES

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF SWALLOWED

Rinse mouth. Do NOT induce vomiting.

If victim is conscious, give 1 – 2 glasses of water.

IF SWALLOWED: Call a POISON CENTER/doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

(Symptoms when inhalation or ingestion)

Nausea. Abdominal pain. Diarrhoea. Cough. Sore throat. Vomiting.

(Symptoms when skin and/or eye contact)

Watering of the eyes. Conjunctival redness of the eyes. Redness of the skin. Pain.

Indication of any immediate medical attention and special treatment needed

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Specific treatment is required.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

In case of fire, use foam, dry powder, CO2 to extinguish.

Unsuitable extinguishing media

Do not use direct water jet.

Water may be effective for cooling, but may not effect extinguishment.

Specific hazards arising from the substance or mixture

Containers may explode when heated.

Fire may produce irritating, corrosive and/or toxic gases.

Runoff from fire control or dilution water may cause pollution.

Advice for firefighters

Specific fire-fighting measures

Evacuate non-essential personnel to safe area.

Cool container with water spray.

Special protective equipment and precautions for fire-fighters

Wear fire resistant or flame retardant clothing.

Wear protective gloves/protective clothing/eye protection/face protection.

Firefighters should wear self-contained breathing apparatus with a full facepiece operated in the positive pressure mode.

Section 6. Accidental release measures

Personnel precautions, protective equipment and emergency procedures

Keep unauthorized personnel away.

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

Ventilate area until material pick up is complete.

Wear proper protective equipment.

PUBLIC SAFETY: Ventilate closed spaces before entering.

Do not touch or walk through spilled material.

Environmental precautions

- Runoff to sewer may create fire or explosion hazard.
- Vapor explosion hazard indoors, outdoors or in sewers.
- Avoid release to headsprings, rivers, lakes, ocean and groundwater.

Methods and materials for containment and cleaning up

- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Use clean non-sparking tools to collect absorbed material.
- All equipment used when handling the product must be grounded.

Preventive measures for secondary accident

- Collect spillage.
- Stop leak if you can do it without risk.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Prevent entry into waterways, sewers, basements or confined areas.
- Keep out of low areas.

Section 7. Handling and storage**Precautions for safe handling****Preventive measures****(Exposure Control for handling personnel)**

- Avoid breathing dust/fume/gas/mist/vapors/spray.

(Protective measures against fire and explosion)

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Ground and bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Use non-sparking tools.
- Take action to prevent static discharges.

(Exhaust/ventilator)

- Exhaust/ventilator should be available.

(Precautions)

- Avoid contact with skin.
- Avoid contact with eyes.

Safety Measures

- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use personal protective equipment as required.
- When using do not eat, drink or smoke.

Any incompatibilities

- Strong acids, Strong oxidizing agents should not be mixed with the chemicals.

Advice on general occupational hygiene

- Contaminated work clothing should not be allowed out of the workplace.
- Take off contaminated clothing and wash it before reuse.

Storage**Conditions for safe storage**

- Store in a well-ventilated place. Keep container tightly closed.
- Keep cool. Protect from sunlight.
- Store in accordance with local/national regulation.
- Store locked up.

Container and packaging materials for safe handling

- Keep only in original packaging.

Specific end use(s)

- See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

Section 8. Exposure controls/personal protection

Control parameters

Control value and Concentration standard value under ISHA

(Methyl methacrylate)

Concentration standard value TWA: 20ppm

Occupational Exposure Limit

JSOH

(Methyl methacrylate)

2ppm; 8.3mg/m³

ACGIH

(Methyl methacrylate)

TWA: 50ppm; STEL: 100ppm (URT & eye irr; body weight eff; pulm edema)

Notation

(Methyl methacrylate)

DSEN

Exposure controls

Appropriate engineering controls

Do not use in areas without adequate ventilation.

Eye wash station should be available.

Washing facilities should be available.

Individual protection measures

Respiratory protection

Select and wear respiratory protection in accordance with approved standards (e.g. JIS T8150).

Recommended respiratory protection: Gas mask

Hand protection

Wear protective gloves. Recommended material(s): impermeable or chemical resistant rubber

Inspect before use and replace worn or damaged gloves.

Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions.

Chemical-resistant, impervious gloves complying with an approved standard (e.g. JIS T8116) should be used.

Eye protection

Wear safety glasses with side-shields.

Wear eye/face protection in accordance with approved standards (e.g. JIS T8147).

Skin and body protection

Wear impervious clothing and boots in case of repeated or prolonged treatment.

Personal protective equipment for the body and skin should be selected based on the task being performed and the risks involved.

Section 9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical state: Liquid

Color: Colorless

Odor: Characteristic odor

Odor threshold data is not available.

Melting point/Freezing point: -75°C

Boiling point or initial boiling point: 117°C

Boiling range data is not available.

Flammability data is not available.

Lower and upper explosion limit/flammability limit:

Lower explosion limit: 1.8 vol %

Flash point: 19°C(Closed cup)

Auto-ignition temperature: 450°C

Decomposition temperature data is not available.

pH data is not available.

Kinematic viscosity data is not available.

Solubility:

Solubility in water: Slightly soluble

Solubility in solvent: Soluble in alcohol.

Partition coefficient n-octanol/water: log Pow1.94

Vapor pressure: 2 kPa (20°C)

Density and/or relative density: 0.911~0.916 g/mL(20°C)

Relative vapor density (Air=1): 3.9

Relative density of the Vapor/air – mixture at 20°C (Air = 1): 1.01

Particle characteristics data is not available.

Section 10. Stability and Reactivity

Reactivity

Runaway polymerization may occur without stabilizer or when heated.

Chemical stability

Stable under normal storage/handling conditions.

Highly flammable.

Possibility of hazardous reactions

The vapour mixes well with air, explosive mixtures are easily formed. Vapours are uninhibited and may polymerize, causing blockage of vents.

The substance may violently polymerize due to warming, under the influence of light and on contact with strong oxidants.

Conditions to avoid

Contact with incompatible materials.

Open flames. Heating. Sparks. Light.

Incompatible materials

Strong acids, Strong oxidizing agents

Hazardous decomposition products

Carbon oxides

Section 11. Toxicological Information

Information on toxicological effects

Acute toxicity

Acute toxicity (Oral)

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

[NITE-CHIRP]

(Ethyl methacrylate)

rat LD50: 12.7 – 18.14 g/kg (source: NITE)

(Methyl methacrylate)

rat LD50: 7800 mg/kg (source: NITE)

Acute toxicity (Dermal)

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

[NITE-CHIRP]

(Ethyl methacrylate)

rabbit LD50: > 9.1 g/kg (source: NITE)

(Methyl methacrylate)

rabbit LD50: > 5000 mg/kg (source: NITE)

Acute toxicity (Inhalation)

[Product]

Category 4, Harmful if inhaled

[Data for components of the product]

[NITE-CHRIP]

(Ethyl methacrylate)

vapor: rat LC50: 8300 ppm (4-hour) (source: NITE)

(Methyl methacrylate)

vapor: rat LC50: 7093 ppm (4-hour) (source: NITE)

Irritant properties

Skin corrosion/irritation

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

[NITE-CHRIP]

(Methyl methacrylate)

Category 2 (source: NITE)

Serious eye damage/irritation

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

[NITE-CHRIP]

(Methyl methacrylate)

Category 2 (source: NITE)

Sensitization

Respiratory sensitization

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

[NITE-CHRIP]

(Methyl methacrylate)

Category 1 (source: NITE)

Skin sensitization

[Product]

Category 1, May cause an allergic skin reaction

[Data for components of the product]

[NITE-CHRIP]

(Ethyl methacrylate)

Category 1 (source: NITE)

(Methyl methacrylate)

Category 1 (source: NITE)

Germ cell mutagenicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Carcinogenicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

[IARC]

(Methyl methacrylate)

Group 3 : Not classifiable as to its carcinogenicity to humans

[ACGIH]

(Methyl methacrylate)

A4: Not Classifiable as a Human Carcinogen

[EPA]

(Methyl methacrylate)

NL; Not likely to be carcinogenic to humans(1996)

Reproductive toxicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Specific target organ toxicity (STOT)

STOT-single exposure

[Product]

Category 3, May cause respiratory irritation

[Data for components of the product]

[NITE-CHRIP]

(Ethyl methacrylate)

Category 3 (Respiratory tract irritation) (source: NITE)

(Methyl methacrylate)

Category 3 (Narcotic effects) (source: NITE)

STOT-repeated exposure

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Aspiration hazard

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

No data available.

Section 12. Ecological Information

Ecotoxicity

Aquatic toxicity

[Product]

Classification not possible (Insufficient data available or no data available).

[Data for components of the product]

Hazardous to the aquatic environment, short-term (acute)

[NITE-CHRIP]

(Methyl methacrylate)

Crustacea (Daphnia magna) 48-hour EC50: 48 mg/L (source: NITE)

Hazardous to the aquatic environment, long-term (chronic)

[NITE-CHRIP]

(Ethyl methacrylate)

Crustacea (Daphnia magna) 21-day NOEC: 18 mg/L (source: NITE)

(Methyl methacrylate)

Crustacea (Daphnia magna) 21-day NOEC (reproduction inhibition): 3.5 mg/L (source: NITE)

Algae (Pseudokirchneriella subcapitata) 72-hour NOEC: 86 mg/L (source: NITE)

Water solubility

[Data for components of the product]

(Ethyl methacrylate)

poor (source: ICSC, 2003)

(Methyl methacrylate)

1.6 g/100 mL (20°C) (source: ICSC, 2003)

Persistence and degradability

[Data for components of the product]

(Methyl methacrylate)

Rapidly degradable (Degradation rate: 94.3% (by BOD)) (source: NITE)

Bioaccumulative potential

[Data for components of the product]

(Ethyl methacrylate)

log Pow: 1.94 (source: ICSC, 2003)

(Methyl methacrylate)

log Kow: 1.38(20°C) (source: NITE)

Mobility in soil

Mobility in soil data is not available.

Other adverse effects

Ozone depleting chemical data is not available.

Section 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Waste treatment methods

Dispose of contents/container in accordance with local/national regulation.

Section 14. Transport Information

UN No., UN CLASS

UN Number or ID Number : 2277

UN Proper Shipping Name : ETHYL METHACRYLATE, STABILIZED

Class or division (Transport hazard class) : 3

Packing group : II

ERG GUIDE No.: 130P

Special provisions No.: 386

IMDG Code (International Maritime Dangerous Goods Regulations)

UN Number or ID Number : 2277

UN Proper Shipping Name : ETHYL METHACRYLATE, STABILIZED

Class or division (Transport hazard class) : 3

Packing group : II

Special provisions No.: 386

IATA (Dangerous Goods Regulations)

UN Number or ID Number : 2277

UN Proper Shipping Name : ETHYL METHACRYLATE, STABILIZED

Class or division (Transport hazard class) : 3

Hazard labels : Flamm. liquid

Packing group : II

Special provisions No.: A209

Environmental hazards

Marine pollutants (yes/no) : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Noxious Liquid Substances ; Cat. Y

Ethyl methacrylate; Methyl methacrylate

Section 15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Labor Standards Act, Japan

Chemical substances or compounds (including alloys) causing disease (item (iv)-1 of Appended Table 1-2 of Regulation)

Methyl methacrylate

Sensitization [MHLW_J Notice]

Methyl methacrylate

U.S. Toxic Substances Control Act (TSCA) Inventory

Chemicals listed in TSCA Inventory

80-62-6; 97-63-2

All components are listed or exempted.

Other regulatory information

We are not able to check up the regulatory information with regard to the substances in your country or region, therefore, we request this matter would be filled by your responsibility.

Regulatory information with regard to this substance in your country or in your region should be examined by your own responsibility.

Ensure this material in compliance with federal requirements and ensure conformity to local regulations.

Regulatory information in this section are limited to intentional ingredient(s), but does not contain information on non-intentional ingredients or impurities which are not informed by supplier(s).

Chemical safety assessment

Advice on safe handling for this product can be found in sections 7 and 8 of this SDS.

Section 16. Other information

GHS classification and labelling

H225-Flammable liquids, Category 2: H225 Highly flammable liquid and vapour

Self-Reactive Substances and Mixtures, Type G

H332-Acute toxicity, Category 4: H332 Harmful if inhaled

H317-Skin sensitization, Category 1: H317 May cause an allergic skin reaction

H335-STOT - single exposure, Category 3, Respiratory tract irritation: H335 May cause respiratory irritation.

References and sources for data

Globally Harmonized System of classification and labelling of chemicals, UN

Recommendations on the TRANSPORT OF DANGEROUS GOODS 23rd edit., 2023 UN

IMDG Code, 2024 Edition (Incorporating Amendment 42-24)

IATA Dangerous Goods Regulations (66th Edition) 2025

2024 EMERGENCY RESPONSE GUIDEBOOK (US DOT)

2025 TLVs and BEIs. (ACGIH)

JIS Z 7252 : 2019

JIS Z 7253 : 2019

Recommendation of occupational exposure limits (2023-2024) (JSOH)

Notification No. 0111-1 (January 11, 2022), Chemical Hazards Control Division, Industrial Safety and Health Department, Labour Standards Bureau, MHLW in Japan

Supplier's data/information

Chemicals safety data management system "GHS Assistant" Version 4.34(<https://www.asahi-ghs.com/>)

NITE Chemical Risk Information Platform "NITE-CHRIIP"

(https://www.chem-info.nite.go.jp/chem/chrip/chrip_search/systemTop)

GHS Classification Guidance for Enterprises 2019 Revised Edition (Ver. 2.1) (May. 2024, METI)

Abbreviations and acronyms

SDS (Safety Data Sheet)

LD50 (Lethal Dose, 50%)

LC50 (Lethal Concentration, 50%)

IARC (International Agency for Research on Cancer)

ACGIH (American Conference of Governmental Industrial Hygienists)

EPA (US Environmental Protection Agency)

NTP (US National Toxicology Program)

METI (Ministry of Economy, Trade and Industry in Japan)

MHLW (Ministry of Health, Labour and Welfare in Japan)

MOE (Ministry of the Environment in Japan)

JSOH (Japan Society for Occupational Health)

ISHA (Industrial Safety and Health Act in Japan)

CSCL (Chemical Substances Control Law in Japan)

EU (European Union)

EC50 (Effective Concentration, 50%)

NOEC (No Observed Effect Concentration)

BOD (Biochemical Oxygen Demand)

COD (Chemical Oxygen Demand)

BCF (Bioconcentration Factor)

anh (anhydride)

General Disclaimer

This data sheet was created based on the information we currently have and may be revised according to new information. In addition, the precautions apply only to normal handling, and in the case of special handling, please make adequate countermeasure to maintain your safety.

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the products' properties.

The GHS classification data given here is based on current Data published in Japan (National Institute of Technology and Evaluation (NITE) Chemical Risk Information Platform (NITE-CHRIIP), up to FY2023).